


Telemetry Charger Module for use with T24



Lithium battery, telemetry charger module and power supply suitable for T24 range



User Benefits

- Allows T24 system to be powered by rechargeable batteries
- Li Ion batteries allow power from 5 V supplies

Ideal Application

- Civil Engineering
- Construction
- Automotive
- Lifting & Weighing
- OEM

Introduction

The T24-BC1 is a battery charger and power supply suitable for the T24 range of 3V devices. The T24 Battery Charger is designed to supply a constant 3.3 V from a Li-ion Battery while also charging the battery from an input voltage.

The unit comes pre-configured to provide a charging current of 466mA suitable for VARTA LIP653450. This module also supports additional batteries providing a charge current of 133 mA via the removal of the leaded resistor (non surface mount).

Please note batteries are not included.

Specification at a Glance

- Lithium battery telemetry charger modules for use with T24 acquisition modules
- Provides 3.3 V regulated output
- Same footprint as T24 acquisition modules
- Charges from 5 VDC supply (ideal for USB)
- Dimensions 37.5 x 16.8 mm



Related Product



T24-TA
Wireless acquisition for temperature measurement equipment



T24-PA
Pulse to wireless telemetry converter



T24-SA
Strain gauge to radio telemetry converter



T24-VA
Voltage to wireless converter



T24-RA
Wireless potentiometer for displacement sensor



T24-IA
Current to radio telemetry converter

Case Study

The Application:

Highway agencies and bridge owners spend large revenues protecting bridge users by visual inspection of bridge elements such as bolt joints and tensile steel ropes.

Obtaining multiple readings to monitoring the entire structure can be costly and labour intensive.

The Solution:

A single bridge can be fitted with low power telemetry acquisition devices at every joint to monitor the strain in bolts and fixings, thus indicating where the bridges' weak points are and when they need servicing. A PC based on the bridge would allow the wireless data to be logged and then remotely accessed over the Internet as well as being able to alert engineers by email to any critical repairs required.



Fitting the bridge with, for example, 12 acquisition devices would allow the T24-HA Advanced Wireless Handheld to be used on-site to view the values of the 12 devices and their instantaneous values. Owing to the low power

requirements of the T24-SA strain gauge acquisition modules, a simple solar panel power supply can be used to trickle-charge the batteries via the T24-BC1 battery charger contained within each unit.

CE & Environmental

Storage temperature	- 40 to +85°C
Operating temperature	- 40 to +85°C
Relative humidity	95% maximum non condensing

CE Environmental Approvals

European EMC Directive	2004/108/EC
Low Voltage Directive	2006/95/EC

For more information contact us today...

mantracourt.com
technical@mantracourt.com
Mantracourt Electronics Ltd
The Drive, Farringdon, Exeter,
Devon, EX5 2JB, UK
tel: +44 (0) 1395 232020
fax: +44 (0) 1395 233190



In the interests of continued product development, Mantracourt Electronics Limited reserves the right to alter product specifications without prior notice